


Xingto Battery 18S30AH Specifications

一. Scope of application

This product specification describes the performance indicators of the solid-state lithium-ion battery pack produced by **Zhuoxun Intelligent Technology (Henan) Co., Ltd.** Note: The solid-state lithium-ion battery pack described in this specification refers to a lithium-ion battery with solid-state technology (solid-liquid hybrid).

二. Product size



Code	Name	size(±5mm)
A	width	198mm
B	Thickness (max).	77mm
C	length	195mm
D	Long leakage line	≥200mm
	Power cord terminals	Optional
	Balance head	Optional

三. Product Specifications

serial number	project		Technical indicators
1	Nominal capacity		30Ah (0.5C)
2	Minimum capacity		29.5Ah (0.5C)
3	Nominal voltage		66.6V
4	Charging voltage		75.6V
5	Termination voltage		45V
6	Charging method	fast	1C (30A) Constant current (CC) Charge to 75.6V, then constant voltage (CV) Charge until the charge current is less than 0.02C (0.60A)
		standard	0.5C (20A) Constant current (CC) Charge to 75.6V, then constant voltage (CV) Charge until the charge current is less than 0.02C (0.60A)
7	Discharge method	pulse	10C (300A、duration≤10S) 5C (150A)
		Magnification	3C (90A)
		standard	0.5C (15A)
8	Operating temperature		Charge: 0°C~45°C Discharge: -10°C~55°C
10	Storage temperature		Short-term storage (1month):-20°C~45°C Long-term storage (6 months) : -10°C~35°C
11	Storage humidity		<75%RH
12	Internal resistance(max)		<18mΩ
13	weight (max)		<5.59 Kg
14	Factory voltage		63V~66.5V
15	Outer carton size		350*270*360(Please refer to the actual situation)
16	Package weight		<12.50 Kg